



CV Compactor Specifications and Dimensions

(800) 678-7320

sales@jv.com

Cram-A-Lot CV Series Compactors SPECIFICATIONS		All CV Models
Charge Box Capacity		Varies by Model
NWRA Rated Size		0.49
Theoretical Cycle Time		37 sec
Total Force	Normal	25,100 lbs
	Max	30,200 lbs
Ram Face Pressure	Normal	15.6 psi
	Max	18.8 psi
Ram Face Dimensions	W x D	48"x 35"
Ram Penetration		21"
Motor - 3 Phase	208/230/460 VAC	3 hp
Motor - 1 Phase	230 VAC	3 hp
Pump Capacity		3 gpm
Hydraulic Reservoir	Capacity	8 gal
Hydraulic Cylinder	Bore Dia.	4"
	Stroke	18"
	Rod Dia.	2"
Operating Pressure	Normal	2,000 psi
	Max	2,400 psi
Complete Unit UL Listed		No

Cram-A-Lot CV Compactors DIMENSIONS	Loading Height	Overall Depth	Overall Width	Overall Height	Clear Top (Length x Width)	Unit Weight
CV-02-FL-FF	56 3/4"	51"	94"	94 1/2"	48"x 25 1/2"	3,450 lbs
CV-02-FL-RF	56 3/4"	51"	94"	94 1/2"	48"x 25 1/2"	3,450 lbs
CV-03-FL-FF	47"	81 1/2"	94"	85"	48"x 25 1/2"	3,460 lbs
CV-03-FL-RF	47"	81 1/2"	94"	85"	48"x 25 1/2"	3,460 lbs
CV-04-FL-FF	47"	81 1/2"	94"	85"	48"x 25 1/2"	3,630 lbs
CV-04-FL-RF	47"	81 1/2"	94"	85"	48"x 25 1/2"	3,630 lbs
CV-06-FL-FF	60"	81 1/2"	94"	98"	48"x 25 1/2"	3,810 lbs
CV-06-FL-RF	60"	81 1/2"	94"	98"	48"x 25 1/2"	3,810 lbs
CV-08-FL-FF	74"	81 1/2"	94"	112"	48"x 25 1/2"	4,150 lbs
CV-08-FL-RF	74"	81 1/2"	94"	112"	48"x 25 1/2"	4,150 lbs