

## Self Contained Compactor Specifications

Cram-A-Lot SC Series Specifications		SC-T1 Models	SC-T2 Models	SC-T2-LP Low Profile Models	SC-02 Models	SC-02-LP Low Profile Models	SC-T2 Hydraulic Tailgate Models	SC-T2.5 Models	SC-T2.5-LP Low Profile Models
Charge Box Capacity		1 cu yd	2 cu yd	2 cu yd	2 cu yd	2 cu yd	2 cu yd	2.5 cu yd	2.5 cu yd
NWRA Rated Size		0.75 cu yd	1.52 cu yd	1.14 cu yd	1.31 cu yd	1.03 cu yd	1.52 cu yd	1.88 cu yd	1.47 cu yd
Theoretical Cycle Time		28 sec	37 sec	37 sec	32 sec	32 sec	37 sec	41 sec	41 sec
Total Force	Normal	44,200 lbs	42,700 lbs	42,700 lbs	39,300 lbs	39,300 lbs	42,700 lbs	42,700 lbs	42,700 lbs
	Maximum	53,000 lbs	51,250 lbs	51,250 lbs	47,100 lbs	47,100 lbs	51,250 lbs	51,250 lbs	51,250 lbs
Ram Face Pressure	Normal	40.0 psi	24.5 psi	31.5 psi	22.6 psi	29.0 psi	24.5 psi	24.5 psi	24.5 psi
	Maximum	48.0 psi	29.5 psi	38.04 psi	27.1 psi	34.8 psi	29.5 psi	29.5 psi	29.5 psi
Ram Face Dimensions (W x H)		48" x 23"	60" x 29"	60" x 23"	60" x 29"	60" x 23"	60" x 29"	60" x 29"	60" x 23"
Ram Penetration		6"	8"	8"	5.5"	5.5"	8"	8"	5.8"
Motor - 3 Phase 208/230/460 VAC		10 hp	10 hp	10 hp	10 hp	10 hp	10 hp	10 hp	10 hp
Pump Capacity		10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm	10.5 gpm
Hydraulic Reservoir Capacity		22 gal	22 gal	22 gal	22 gal	22 gal	22 gal	22 gal	22 gal
Hydraulic Cylinder	Bore Dia.	(two) 4"	(two) 4"	(two) 4"	5"	5"	(two) 4"	(two) 4"	(two) 4"
	Stroke	26"	34"	34"	40"	40"	34"	41"	41"
	Rod Dia.	2"	2"	2"	2.5"	2.5"	2"	2.5"	2.5"
Operating Pressure	Normal	2000 psi	2000 psi	2000 psi	2000 psi	2000 psi	2000 psi	2000 psi	2000 psi
	Maximum	2400 psi	2400 psi	2400 psi	2400 psi	2400 psi	2400 psi	2400 psi	2400 psi

Cram-A-Lot SC Series Dimensions	Overall Length	Packer Length	Clear Top (Length X Width)	Base Unit Weight	Base Unit Weight (LP Models)	Normal Container Capacity
SC-T1-10	13' 2"	60"	31"x 46"	6,500 lbs	N/A	10 cu yd
SC-T1-15	16' 6"	60"	31"x 46"	7,000 lbs	N/A	15 cu yd
SC-T1-20	19' 10"	60"	31"x 46"	7,500 lbs	N/A	20 cu yd
SC-T2-15	15'	71"	41"x 58"	8,900 lbs	8,770 lbs	15 cu yd
SC-T2-20	17' 4"	71"	41"x 58"	9,800 lbs	9,670 lbs	20 cu yd
SC-T2-25	19' 11"	71"	41"x 58"	10,000 lbs	9,870 lbs	25 cu yd
SC-T2-30	22' 1"	71"	41"x 58"	10,800 lbs	10,670 lbs	30 cu yd
SC-T2-34	23' 9"	71"	41"x 58"	10,900 lbs	10,770 lbs	34 cu yd
SC-T2-38	25' 10"	71"	41"x 58"	12,000 lbs	11,870 lbs	38 cu yd
SC-02-30	19'	90 1/2"	34"x 58"	9,860 lbs	9,680 lbs	20 cu yd
SC-02-25	21' 7"	90 1/2"	34"x 58"	10,100 lbs	9,920 lbs	25 cu yd
SC-02-30	23' 9"	90 1/2"	34"x 58"	10,800 lbs	10,630 lbs	30 cu yd
SC-02-34	25' 5"	90 1/2"	34"x 58"	10,900 lbs	10,720 lbs	34 cu yd
SC-T1-16-HTG	18'	60"	31"x 46"	8,000 lbs	N/A	16 cu yd
SC-T1-20-HTG	19' 8"	60"	31"x 46"	8,200 lbs	N/A	20 cu yd
SC-T1-25-HTG	23'	60"	31"x 46"	8,900 lbs	N/A	25 cu yd
SC-T2-20-HTG	17'	71"	41"x 58"	10,260 lbs	N/A	20 cu yd
SC-T2-25-HTG	19' 7"	71"	41"x 58"	10,900 lbs	N/A	25 cu yd
SC-T2-30-HTG	21' 9"	71"	41"x 58"	11,540 lbs	N/A	30 cu yd

SC-T2.5-25	21' 6"	90"	48"x 58"	10,000 lbs	9,870 lbs	25 cu yd
SC-T2.5-30	23' 8"	90"	48"x 58"	10,800 lbs	10,670 lbs	30 cu yd
SC-T2.5-34	25' 4"	90"	48"x 58"	10,900 lbs	10,770 lbs	34 cu yd



(800) 678-7320

sales@jv.com