



Space Saver Compactor Specifications and Dimensions

(800) 678-7320

sales@jv.com

Cram-A-Lot 2 - 4 Yard Stationary Compactor SPECIFICATIONS		CSX-02	CSX-2.5	CSX-03
Charge Box Capacity		2 cu yd	2.5 cu yds	3 cu yds
NWRA Rated Size		1.51	1.92	2.43
Theoretical Cycle Time		50 sec	63sec	76 sec
Total Force	Normal	54,070 lbs	55,280 lbs	54,940 lbs
	Maximum	64,880 lbs	66,330 lbs	65,930 lbs
Ram Face Pressure	Normal	32.8 psi	33.2 psi	33 psi
	Maximum	39.3 psi	39.8 psi	39.6 psi
Ram Face Dimensions	W x H	60"x 27 3/4"	60"x 27 3/4"	60"x 27 3/4"
Ram Penetration		13"	14"	14"
Motor - 3 Phase	208/230/460 VAC	10 hp	10 hp	10 hp
Pump Capacity		10.5 gpm	10.5 gpm	10.5 gpm
Hydraulic Reservoir	Capacity	22 gal	22 gal	22 gal
Hydraulic Cylinder	Bore Dia.	4 1/2"	4 1/2"	4 1/2"
	Stroke	38"	48"	57 1/4"
	Rod Dia.	2 1/2"	2 1/2"	2 1/2"
Operating Pressure	Normal	2,000 psi	2,000 psi	2,000 psi
	Maximum	2,400 psi	2,400 psi	2,400 psi
Complete Unit UL Listed		No	No	No

Cram-A-Lot 2 - 4 Yard Stationary Compactor DIMENSIONS	Overall Length	Overall Width	Loading Sill Height	Overall Height	Ground Height	Clear Top (Length x Width)	Base Unit Weight
CSX-02	6'	58"	48"	54"	15"	42"x 58"	4,400 lbs
CSX-2.5	7' 7"	58"	48"	54"	15"	53 1/2"x 58"	4,885 lbs
CSX-03	9' 4 1/2"	58"	48"	54"	15"	68"x 58"	5,435 lbs